

Nu-Wall Aluminium Cladding – Installation Reference (vertical on cavity)

1

Introduction

This installation reference offers guidelines for the application of Nu-Wall over new timber frame constructions, or for re-cladding of existing structures. Nu-Wall can also be installed over steel framing and other substrates, including over-cladding. While not all are covered in this document and referenced drawings, assistance is available with detailing of such specifications.

This document is designed to be used in conjunction with published specification drawings, copies of which are available upon request; alternatively they may be downloaded in PDF format from the website – www.nu-wall.co.nz. For best results and a weather-tight outcome, please study the details carefully with particular attention to procedures at details such as corners and around window and door penetrations. Nu-Wall is essentially a weatherboard product; the only fabrication required prior to installation being cutting to length and some longitudinal ripping of the extruded profiles. As such, installation should be well within the capabilities of a competent builder.

Please refer to the document “Nu-Wall Aluminium Cladding – General Information” for advice on the selection and care of the product’s pre-finished surface.

Preparation

Before starting any installation check the following:

That all components are stored safely and securely off the ground in dry conditions and away from potential damage or theft. It is easier to protect the pre-finished products than to repair or replace them.

Ensure all safety equipment is at hand; e.g. eye- and ear-protection, and that you follow established safe practice with access equipment.

Ensure that you are fitting the cladding over a wall underlay complying with NZBC Acceptable Solution E2/AS1 Table 23. There is no moisture absorbency requirement for wall underlays used behind Nu-Wall weatherboards when they are installed over a drained and vented cavity. Wall underlay must be installed horizontally and be continuous around corners. The underlay must be lapped 75 mm minimum at horizontal joints and 150 mm minimum over studs at vertical joints.

All buildings must have barriers to airflow in the form of interior linings with all joints stopped, or alternatively, unlined gables and walls must incorporate a rigid

sheathing or an air barrier which meets the requirements of NZBC Acceptable Solution E2/AS1, Table 23. Where rigid sheathings are used, the fixing length must be increased by a minimum of the thickness of the sheathing.

Handling and storage

Nu-Wall weatherboards and accessories must be stacked flat, off the ground and supported on a level platform. They must be kept dry either by storing under cover or providing waterproof covers to the stack. Care must be taken to avoid damage to powder coated surfaces. Nu-Wall weatherboards must always be carried on edge.

Other accessories must be stored so they are kept clean, dry and undamaged. All accessories must be used within the maximum storage period recommended by the manufacturer.

Layout

Where drawings and/or other information have been supplied, indicating the layout and utilisation of boards and offcuts, these will have been prepared from scale drawings, necessitating certain judgements regarding dimensions. Such information should be viewed as a guide only; dimensions should be verified by measuring on-site.

Tools

The following should suffice for most situations –

- Hammer and appropriate nail punch.
- Level or dumpy level.
- Chalk line.
- Drop-and-draw saw for cutting profiles to length, plus skilsaw, hacksaw, and preferably a jigsaw for ripping and detailing. Ensure all saws are equipped with blades appropriate for cutting aluminium.
- Mastic gun and tinsnips.
- Electric drill with square drive & 5mm drill bits.

Building regulations

The Nu-Wall cladding systems if designed, used and installed in accordance with the statements and conditions of this literature and the supporting BRANZ Appraisal, will meet the following provisions of the New Zealand Building Code:

- Clause B1 Structure
- Clause B2 Durability
- Clause E2 External Moisture
- Clause F2 Hazardous Building Materials

Nu-Wall Aluminium Cladding – Installation Reference (vertical on cavity)

2

Structure and framing

Timber framing must comply with NZS 3604 for buildings or parts of buildings within the scope limitations of NZS 3604. Buildings or parts of buildings outside the scope of NZS 3604 must be to a specific design in accordance with NZS 3603 and AS/NZS 1170. Where specific design is required, the framing must be of at least equivalent stiffness to the framing provisions of NZS 3604. In all cases studs must be at maximum 600 mm centres. Dwangs must be fitted flush between the studs at maximum 600 mm centres for Nu-Wall weatherboards installed in a vertical orientation.

Steel framing must be to a specific design meeting the requirements of the NZBC. The minimum framing specification is 'C' section studs and nogs of overall section size of 75 mm web and 32 mm flange. Steel thickness must be minimum 0.55 mm. In all cases, studs must be at maximum 600 mm centres. Dwangs must be fitted flush between the studs at maximum 600 mm centres for Nu-Wall weatherboards installed in a vertical orientation.

Fixing requirements

The Nu-Wall Universal Fixing Bracket, used as specified, has been verified for Wind Zones up to and including Extra High on structures within the scope of NZS3604. Projects which are outside of this scope would be the subject of specific design, possibly requiring an increased fixing density; this should have been specified during the design process.

Inter-storey junctions

Inter-storey drained joints must be provided to limit continuous cavities to the lesser of 2 storeys or 7.0 metres in height, in accordance with the requirements of NZBC Clause E2/AS1, Paragraph 9.1.9.4(b).

Installation

The Nu-Wall Vertical Cavity System must incorporate a PVC or aluminium vent strip, punched with 3-5mm holes or slots complying with NZBC Clause E2/AS1, Paragraph 9.1.8.3. The vent strip must provide a minimum ventilation opening area of 1000 mm² per lineal metre of wall.

Cavity battens should be installed over the building underlay to the wall framing horizontal dwangs at maximum 600 mm centres. Battens should be of minimum finished size 45mm wide by 18mm thick, and must permit air passage through and water drainage. The battens must be fixed in place with 40 x 2.5 mm

hot-dipped galvanised flat head nails at maximum 800mm centres. Flexible building underlay must be supported between the battens to prevent the underlay bulging into the cavity space when bulk insulation is installed in the wall frame cavity.

See Note 1 at the end of this document regarding use of treated timber battens.

Recommended fixing sequence

Ensure that dwangs have been installed at 600mm spacing wherever the Nu-Wall cladding is to be installed in order to enable compliance with fixing specifications.

Where Nu-Wall cladding is installed vertically, normal procedure is to install joinery units after cladding.

Prior to construction of the drainage cavity, the joinery head flashings should be fitted – see drawings NW-V012C – V014C for guidance.

If using treated timber battens, tack the barrier strip (MDPE or similar) in place over all battening where contact will occur with the cladding or other extruded aluminium sections.

Fix any supplementary flashings required, such as at junctions with other cladding materials etc.

Clips for all corners and vertical joints.

Jamb flashing base to door jambs.

Jamb flashing base / J-mould at cladding junctions.

Base channel between vertical jointer and corner clips.

Drainage soaker strip to head/jamb/sill.

Jamb flashing base to window jambs.

Jamb flashing caps

Nu-Wall boards.

Second piece of all remaining two part jointers and trims.

Note: Some jobs may not include all of the above steps.

Fitting the initial fixing sections

Please refer to specification drawings NW-P001 – P010 for identification of these sections.

The base channel

Refer to drawings NW-V002C – V006C. Establish the lowest point from which the cladding is to start and ensure that the base channel can extend below the bottom plate by the minimum 50mm required by the NZ Building Code. Mark out the position of the base channel to a precise level line that can extend right

Nu-Wall Aluminium Cladding – Installation Reference (vertical on cavity)

3

around the structure. The base channel should be fixed through the cavity battens to the bottom plate as depicted in the drawing. Leave short gaps in the base channel, sufficient to allow vertical joints and corner clips to come to the same bottom level. This detail is depicted in the isometric drawing NW-V006C. Fit the initial side of the corners and vertical joints to the framing, having first tacked in place any supplementary flashing material. Leave the second part of the two piece trims to be clipped in place after all of the boards have been installed.

Installing the Nu-Wall boards

For ease of installation and the best finished result, set out each wall or span to be clad before commencing to cut or fix boards. Plan wherever possible for the full, maximum thickness of the cladding to occur wherever there is a vertical break, such as a corner, window or door jamb, or junction with another cladding material. This will be more challenging with some Nu-Wall profiles than others, however achievement of this will result in a tidy appearance and will facilitate sealing between the cladding face and the capping sections. Ensure that the specified foam sealant tape is installed behind the board at all points where a board meets a vertical detail. See drawings NW-V006C – V008C & NW-V011C for guidance. Fixing is generally as for horizontal application, using the Nu-Wall Universal Fixing Bracket at maximum 600mm vertical centres.

Cutting aluminium

Nu-Wall is no more difficult to cut than timber weatherboards. For most cutting a power saw, fitted with a purpose-made tungsten carbide blade, having a minimum of 60 teeth, negative rake, should be employed. All other sawing equipment should also be fitted with blades suitable for cutting aluminium. Use of timber cutting blades with Nu-Wall is not recommended.

Key Points

- Maintain safe work practices.
- Store the product where it will be protected from damage and secure from theft.
- Determine the specific fixing sequence and set-outs for your job prior to commencement.
- When handling and cutting, take care to protect the pre-finished surface and double check measurements before cutting. Return off-cuts to storage – they may be required for use elsewhere on the job.
- Ensure base channel is fitted to a precise level line around the building, or work from an accurate datum if levels vary.

- Maintain expansion clearances as indicated on detail drawings.
- Frequently check boards for level or plumb and fix correctly to avoid distortion or cupping.
- Follow good trade practices and general principles relating to cladding and weather-tightness.
- Nu-Wall installation information supplied in this document and referenced drawings cannot cover every conceivable situation and our free-phone line – 0800 NUWALL - is available should you require assistance with any detail specification.
- Responsibility for final weathertightness and compliance with all local or national regulations lies with the builder / installer.