



Flexible flashing tape over flashing upstand

2x 2.8x50mm hot dipped galvanised clout nails in to nog framing @ 600 centres. (SS for Exposure Zone D) (2 nails per batten)

H3.2 vertical timber batten  
\*See note

Cavity closer as per E2/AS1 (By others)

Nu-Wall Fascia - can match wall cladding

**NC134P**  
Pre-slotted base channel. Providing 2000mm<sup>2</sup> of ventilation per linear meter

**Optional cavity closure:**  
Use standard 15mm head flashing see NW-VOC-029b

30min

10mm drip edge

Soffit by others

**NC138 + NC139**  
Termination flashing base and cap.

**NC204**  
10g x 16mm csk Tek screw @ 600 centers through anti-crush button

2.8x50mm hot dipped galvanised clout nails @ 600 centers. (SS for Exposure Zone D)

Ripped board

**NC226**  
Impervious barrier between batten & cladding

Drained and vented cavity as per E2/AS1

**NC203E**  
Fixing bracket @ 600mm centers

**NC204**  
10g ss csk screws with 30mm min embedment

30min

**General note:**

- Cladding fixings omitted for clarity

**Cavity batten note:**

- 20mm timber battens required for all Nu-Wall horizontal board installations
- Batten to have 15° slope for moisture egress
- Battens to all internal, external corners, jambs, and sills to be sized to 18mm to accommodate flashing build up
- 20 and 18mm single castellated battens are available directly from Nu Wall
- Proprietary Nu-Wall AliBat is available as an alternative when a structural non-combustible batten is required



	<p>Nu-Wall cladding horizontal on cavity</p> <p>Typical Nu-Wall fascia to soffit</p>	<p>NW-HOC-029.02</p>	
	<p>© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited</p>	<p>Drawn by: Nu-Wall</p> <p>Checked by: RL, GT</p>	<p>Date: 20/9/22</p> <p>Scale: 1:2 @ A4</p>