

2.8x50mm hot dipped galvanised clout nails @ 600 centers.
(SS for Exposure Zone D)

NC203E
fixing clip @ 600 centers

NC 204
10g x 16mm csk Tek screw @ 600 centers through anti-crush packer (by others)

Last board ripped to fit

NC 251
1 Piece External corner 35mm x 70mm

NC 256F
Prefabricated closure for top and bottom

NC 250
Square termination flashing

NC 232 F
Starter bracket

Wall underlay

NC226
Impervious barrier between batten & cladding

Single castellated timber batten
*See note

Drained and vented cavity as per E2/AS1

NC204
10g ss csk screws with 30mm min embedment


Direction of installation →

30min

30min

Direction of installation ↓

NC232F



Starter Bracket used to commence cladding (snapped)

Cavity batten note:

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required



Nu-Wall cladding vertical on cavity
External 90 deg corner using NC251 box assembly

NW-VOC-011.02

Drawn by: Nu-Wall Date: 19/9/2024

Checked by: RL, GT Scale: 1:2 @ A4

© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited