



**General note:**

- Cladding fixings omitted for clarity

**Window setting out notes:**

- 17-18mm for hollow fin windows
- 18-20mm for solid fin windows

**Cavity batten note:**

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- Allow 6mm gap between vertical and horizontal battens
- Sill and head battens to be max. 500mm with a 6mm gap to each segment
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required

Interactive assembly  
instructions available  
<http://wksp.nz/nw-hoc-win>



Get **WORKINGSPEC** from  
Apple App Store/Google Play



**Nu-Wall cladding horizontal on cavity**

**Typical jamb section - NC247 and NC248 assembly**

© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited

**NW-HOC-016.02**

Drawn by: Nu-Wall

Date: 25/02/2025

Checked by: RL, GT

Scale: 1:2 @ A4

**nu-wall**  
CLADDING